

Dustproof



Waterproof



IP56/68 Rating

Dustproof & Waterproof Fan Series 高防护風扇系列

IP-68

- 8：于一定压力下长时间浸水
- 6：完全防止粉尘进入

尺寸 (mm)	机型 (IP56)	机型 (IP68)	额定电压 (VDC)	轴承 ● 2 BALL	转速 (RPM)	风量 (CFM)	风压 (Inch-H2O)	噪音 (db(A))	重量 (g)
60x60x15	GF60151B6-1E00C-AC9	GF60151B6-1E00C-AE9	12	●	4500	21.3	0.18	34.5	47.0
	GF60151B7-1E00C-AC9	GF60151B7-1E00C-AE9	12	●	3900	18.2	0.13	29.8	47.0
	GF60151B8-1E00C-AC9	GF60151B8-1E00C-AE9	12	●	3200	14.5	0.09	24.9	47.0
	GF60151B9-1E00C-AC9	GF60151B9-1E00C-AE9	12	●	2300	10.6	0.05	17.1	47.0
Ø84.9X15.4	GF60151B9-1E01C-AC9	GF60151B9-1E01C-AE9	12	●	2200	9.8	0.05	17.1	45.0
	GF80251B1-000C-AC9	GF80251B1-000C-AE9	12	●	4800	60.0	0.41	47.5	105.0
	GF80251B2-000C-AC9	GF80251B2-000C-AE9	12	●	4500	57.0	0.35	46.0	105.0
	GF80251B3-000C-AC9	GF80251B3-000C-AE9	12	●	4200	53.0	0.30	44.5	105.0
	GF80251B5-000C-AC9	GF80251B5-000C-AE9	12	●	3200	41.0	0.18	33.0	87.0
	GF80251B6-000C-AC9	GF80251B6-000C-AE9	12	●	2900	37.0	0.15	30.0	87.0
	GF80251B7-000C-AC9	GF80251B7-000C-AE9	12	●	2600	33.0	0.11	28.0	87.0
	GE80252B1-000C-AC9	GE80252B1-000C-AE9	24	●	4800	60.0	0.41	47.5	105.0
	GE80252B2-000C-AC9	GE80252B2-000C-AE9	24	●	4500	57.0	0.35	46.0	105.0
	GE80252B3-000C-AC9	GE80252B3-000C-AE9	24	●	4200	53.0	0.30	44.5	105.0
	GF80252B5-000C-AC9	GF80252B5-000C-AE9	24	●	3200	41.0	0.18	33.0	87.0
	GF80252B6-000C-AC9	GF80252B6-000C-AE9	24	●	2900	37.0	0.15	30.0	87.0
	GF80252B7-000C-AC9	GF80252B7-000C-AE9	24	●	2600	33.0	0.11	28.0	87.0
	GE80254B1-000C-AC9	GE80254B1-000C-AE9	48	●	4800	60.0	0.41	47.5	105.0
	GE80254B2-000C-AC9	GE80254B2-000C-AE9	48	●	4500	57.0	0.35	46.0	105.0
	GE80254B3-000C-AC9	GE80254B3-000C-AE9	48	●	4200	53.0	0.30	44.5	105.0
80x80x32	GF80321B1-000C-AC9	GF80321B1-000C-AE9	12	●	4800	59.4	0.36	45.2	109.0
	GF80321B2-000C-AC9	GF80321B2-000C-AE9	12	●	4500	55.9	0.32	43.1	109.0
	GF80321B3-000C-AC9	GF80321B3-000C-AE9	12	●	4100	50.3	0.27	41.1	109.0
92x92x25	GF92251B1-000C-AC9	GF92251B1-000C-AE9	12	●	4500	75.0	0.35	47.0	113.0
	GF92251B2-000C-AC9	GF92251B2-000C-AE9	12	●	4200	70.0	0.30	45.0	113.0
	GF92251B3-000C-AC9	GF92251B3-000C-AE9	12	●	3900	65.0	0.25	43.0	113.0
	GF92251B5-000C-AC9	GF92251B5-000C-AE9	12	●	3000	51.5	0.15	34.0	99.0
	GF92251B6-000C-AC9	GF92251B6-000C-AE9	12	●	2700	45.0	0.13	32.0	99.0
	GF92251B7-000C-AC9	GF92251B7-000C-AE9	12	●	2400	39.5	0.10	28.0	99.0
	GE92252B1-000C-AC9	GE92252B1-000C-AE9	24	●	4500	75.0	0.35	47.0	113.0
	GE92252B2-000C-AC9	GE92252B2-000C-AE9	24	●	4200	70.0	0.30	45.0	113.0
	GE92252B3-000C-AC9	GE92252B3-000C-AE9	24	●	3900	65.0	0.25	43.0	113.0
	GF92252B5-000C-AC9	GF92252B5-000C-AE9	24	●	3000	51.5	0.15	34.0	99.0
	GF92252B6-000C-AC9	GF92252B6-000C-AE9	24	●	2700	45.0	0.13	32.0	99.0
	GF92252B7-000C-AC9	GF92252B7-000C-AE9	24	●	2400	39.5	0.10	28.0	99.0
	GE92254B1-000C-AC9	GE92254B1-000C-AE9	48	●	4500	75.0	0.35	47.0	113.0
	GE92254B2-000C-AC9	GE92254B2-000C-AE9	48	●	4200	70.0	0.30	45.0	113.0
	GE92254B3-000C-AC9	GE92254B3-000C-AE9	48	●	3900	65.0	0.25	43.0	113.0



Meets GR487

符合GR487盐雾测试标准，盐雾环境下适用

环境测试：符合GR-487-CORE(2000), Section3.34.1 Salt Fog Test Procedure.

■ 应用产业：电信网通设备、光伏逆变器、户外LED照明

尺寸 (mm)	机型	额定电压 (VDC)	轴承 ◆ 2 BALL	转速 (RPM)	风量 (CFM)	风压 (Inch-H2O)	噪音 (db(A))	重量 (g)
80x80x25	GF80251B5-000C-AD9	12	◆	3200	41.0	0.18	33.0	87.0
	GF80251B6-000C-AD9	12	◆	2900	37.0	0.15	30.0	87.0
	GF80251B7-000C-AD9	12	◆	2600	33.0	0.11	28.0	87.0
	GF80252B5-000C-AD9	24	◆	3200	41.0	0.18	33.0	87.0
	GF80252B6-000C-AD9	24	◆	2900	37.0	0.15	30.0	87.0
	GF80252B7-000C-AD9	24	◆	2600	33.0	0.11	28.0	87.0
92x92x25	GF92251B5-000C-AD9	12	◆	3000	51.5	0.15	34.0	99.0
	GF92251B6-000C-AD9	12	◆	2700	45.0	0.13	32.0	99.0
	GF92251B7-000C-AD9	12	◆	2400	39.5	0.10	28.0	99.0
	GF92252B5-000C-AD9	24	◆	3000	51.5	0.15	34.0	99.0
	GF92252B6-000C-AD9	24	◆	2700	45.0	0.13	32.0	99.0
	GF92252B7-000C-AD9	24	◆	2400	39.5	0.10	28.0	99.0

台湾建准集团 中国地区

深圳办事处
电话：0755-26880688

上海办事处
电话：158-9566-1206

武汉办事处
电话：027-81388268

北京办事处
电话：010-62669511

2016/07/30 (239-C)

※ 如有特殊规格需求，请与Sunon业务人员联络

※ 此产品目录之规格仅供参考，如有变更无法预先通知。更多Sunon产品信息请至SUNON网站 www.sunon.com.cn，或来信询问 sunon@email.sunon.com.tw

Copyright © 2016 Sunonwealth Electric Machine Industry Co., Ltd